



- Simple and convenient configuration via Web GUI
- Abundant Log Features
- Open API interface (AMI)
- Support T.38 fax relay and T.30 fax transparent, can continually fax multiple pages
- Echo cancellation and Static jitter buffer
- Support DTMF relay
- Support Ring cadence and frequency setting
- Support volume control
- Support MWI (Message waiting indicator)
- Support DHCP、DNS/DDNS、NAT networking
- Support diverse SIP protocols
- Diverse extensible applications, such as IVR,DISA
- Support NTP time synchronization and client time synchronization
- Support modify username and password for web login
- Support SSH remote operation
- Support SRTP
- Support SIP server mode
- Support update firmware online
- Support configuration file backup and upload
- Support for custom scripts, dialplans
- Support restore the factory settings
- Affordable Price with Superior Performance
- Hot-swap Design for Modules
- Compatible with Asterisk, Elastix, 3CX, FreeSWITCH Sip Server and VOS VoIP operating platform
- Available for OEM
- 3-Month "No Questions Asked" Return Policy
- One Year Warranty

AIU-16 Gateway Module

Overview

AIU-16 Gateway Module allowing to support PSTN connection to the VoIP devices, module offers 16 FXS channels.

They can bring you excellent HD voice service with multiple codecs, including G.711U, G.711A, GSM, G.722, G.723, G.726, G.729. AIU-16 Gateway Module will be 100% compatible with Asterisk, 3CX, FreePBX, FreeSWITCH and VOS VoIP operating platform, and help users reduce telecommunications and communication costs.

Technical Specifications

- Dimension: 158mm*100mm
- Weight: 189g
- Max Power Consumption: 20W
- Storage temperature range: -40~125°C
- Operation temperature range: 0~50°C
- Operation humidity range: 10%~90%

