



MAG2000 Series Analog Gateway

Overview

OpenVox MAG2000 is a multifunctional analog gateway for seamless connection between IPPBX, fax machines, analog phones and operators. It provides three interfaces of RJ11/RJ45/RJ21, covering almost all the wiring needs of users in all scenarios. In addition, it has excellent full concurrent voice/ fax processing capabilities, strong performance and high stability, and provides high-quality call services for operators, enterprises, call centers and residential users in residential communities.

The MAG2000 Analog Gateways are developed for interconnecting a wide selection of codecs including G.711A/U, G.723.1, G.729A, G.722, iLBC, OPUS, AMR and AMR-WB. MAG2000 series use standard SIP protocol and compatible with Leading VoIP platform, IPPBX and SIP servers, such as Asterisk, Issabel, 3CX, FreeSWITCH, BroadSoft and VOS VoIP operating platform.



Key features

- 16/24/32 FXS/FXO ports
- Support SNMP and TR069
- Support IPv4 and IPv6
- 3km Line Length
- G.711A/U, G.723.1, G.729A, G.722, iLBC, OPUS, AMR and AMR-WB
- Support API
- Fully Compatible with leading SIP based VoIP Telephony System
- VEX (Advanced Peer To Peer Call)

Physical Interfaces

Capacity

- 16/24/32 FXS with RJ11 & RJ21 & RJ45
- 16/24/32 FXO with RJ11 & RJ21 & RJ45

Ethernet Interfaces:

- 1 * WAN, 10/100/1000Mbps, RJ-45
- 3 * LAN, 10/100/1000Mbps, RJ-45

Voice & FAX

- G.711A/U, G.723.1, G.729A/B, G.722, G726-32, iLBC, OPUS, AMR and AMR-WB
- Comfort Noise Generation(CNG)
- Modem/POS
- Adaptive (Dynamic) Jitter Buffer
- Programmable Gain Control
- DTMF mode: Signal/RFC2833/INBAND
- T.38/Pass-through
- Echo Cancellation(G.168), with up to 128ms

Call Features

- Call Waiting
- Blind Transfer
- Attend Transfer
- Call Forward on Busy
- Call Forward on No Reply
- Unconditional Call Forward
- Warm/Immediately Hotline
- Message Waiting Indicator
- SIP registration to different servers
- Call Hold
- Do-not-disturb
- 3-Way Conference
- Speed Dial

FXS

- Connector: RJ11 & RJ21 & RJ45
- Dial Mode: DTMF and Pulse
- Pulse: 10 and 20 PPS
- Caller ID: DTMF/FSK CLI Presentation
- Max Cable Length: 3 km
- Reversed Polarity Programmable Call Progress Tone

FXO

- Connector: RJ11 & RJ21 & RJ45
- Dial Mode: DTMF/Pulse Dialing
- Caller ID: FSK, DTMF
- Polarity Reversal
- Answer Delay
- Busy Tone Detection
- No Current Detection

Software Features

- Hunting Group
- Web ACL
- Telnet ACL
- Action URL
- PPPoE
- OpenVPN
- Digitmap
- Routing Rules based Prefixes
- Caller/Called Number Manipulation
- VEX (Advanced Peer To Peer Call)
- Voice Activity Detection (VAD)
- Hook Flash
- IMS/3GPP: Conference (3GPP TS 24.147 V8.2.0), IMS Services (3GPP TS24.173 V8.4.0)

VoIP

Protocol:

- SIP v2.0 (UDP/TCP), RFC3261
- SDP,RTP(RFC2833), RFC3262, RFC3263, RFC3264, RFC3265, RFC3515, RFC2976, RFC3311
- RTP/RTCP, RFC2198, RFC1889, RFC 1890
- ETC (3GPP TS 24.629, RFC 3891, RFC 3892)
- IPv4 and IPv6
- Outbound Proxy
- RFC2806 TEL URI
- RFC3581 NAT,rport
- VLAN 802.1P/802.1Q
- RFC4028 Session Timer
- DNS SRV/A Query/NATPR Query
- NAT:STUN, Static/Dynamic NAT

Maintance

- SNMP v1/v2/v3
- Auto Provisioning
- Web Configuration
- Backup/Restore
- Firmware Upgrade via Web
- CDR
- TR069
- IPoE
- Syslog(Emerg,alert, critical,error warning,notice,info, debug)
- Ping/Tracert Test
- Network Capture
- NTP/Daylight Saving Time
- IVR local Maintenance
- Cloud-based Management
- Support Primary and Backup SIP Server

OpenVox MAG2000 Series Analog Gateway

Product Name	MAG2000-16	MAG2000-24	MAG2000-32
--------------	------------	------------	------------

Interfaces

FXS/FXO Ports	16/24/32
Port type	RJ11/RJ45/RJ21
Consloe	RJ45
Ethernet port	4 * 10/100/1000Mbps ports

General Info

Weight (with packaging)	2.20kg	2.32kg	2.44kg
Dimension (bare)	440mm*44.45mm*220mm		
Dimension (with packaging)	510mm*90mm*310mm		
Maximum power	28W	40W	52W
Universal Power Supply	100 ~ 240V AC / -48~-60V DC		
Operation Temperature	0°C ~ 45°C		
Operation Humidity Range	10% ~ 90% NON-CONDENSING		
Storage Temperature Range	-20°C ~ 70°C		
Short/Long Haul Ring Load	2 REN, up to 3km on 24 AWG line		
Certification	CE & FCC		

OpenVox Communication Co.,Ltd.

Website: www.openvoxtech.com

Addr.: Room 624, 6/F, Tsinghua Information Port, Book Building,
Qingxiang Road, Longhua Street, Longhua District, Shenzhen, Guang-
dong, China 518109

Copyright©OpenVox Inc. All rights reserved.

