

# **OCTVQE**

## **Zaptel Echo Cancellor**

### **(PRELIMINARY)**

### **User's Guide**

## Table Of Contents

<b>1</b>	<b>INTRODUCTION .....</b>	<b>3</b>
<b>2</b>	<b>FEATURES LIST .....</b>	<b>4</b>
2.1	Echo Cancellation and Voice Quality Enhancement .....	4
2.2	Linux Application and Kernel Module .....	4
2.3	Performance.....	4
<b>3</b>	<b>INSTALLATION .....</b>	<b>5</b>
3.1	System Requirements.....	5
3.2	Downloading Archive.....	6
3.3	Archive Contents .....	6
3.4	Building and Installing the Octvqe Module.....	8
3.5	Rebuilding and Installing the Zaptel Module .....	8
3.6	Registering the Octvqed Service .....	9
3.7	Starting the Octvqed Service .....	11
3.8	Automatic Startup Script .....	11
<b>4</b>	<b>CHANNEL CONFIGURATION.....</b>	<b>13</b>
4.1	Default Configuration.....	13
4.2	Configuration File .....	13
<b>5</b>	<b>STATISTICS.....</b>	<b>14</b>
<b>6</b>	<b>SOFTWARE UPDATE .....</b>	<b>15</b>
<b>7</b>	<b>REVISION HISTORY .....</b>	<b>16</b>

# 1 INTRODUCTION

The OCTVQE Zaptel Echo Celler is a software package that consists of a Linux executable that performs echo cancellation on systems that use the Zaptel driver. The application communicates with the Zaptel driver through a kernel module.

The application provides industry-leading echo cancellation and voice quality enhancements for systems that rely on the Zaptel driver.

## 2 FEATURES LIST

### 2.1 Echo Cancellation and Voice Quality Enhancement

- Acoustic echo cancellation
- Line echo cancellation - 128 ms tail echo cancellation
- Excellent subjective quality in all conditions
- High quality NLP with spectral comfort noise

### 2.2 Linux Application and Kernel Module

- Linux 2.4 and 2.6 Kernel series support on x86 and x86-64 CPUs
- Up to 8 simultaneous channels
- Latency of 20 milliseconds
- Easy channel monitoring and recording of live voice streams
- Software upgradeable

### 2.3 Performance

The OCTVQE Zaptel Echo Cancellor was benchmarked on various systems. The table below provides some metrics of the average CPU time required for some common processors, for the default channel configuration.

CPU	Average time to process 20 ms
Intel ® Pentium 4 ® 3.0 GHz	448 us
AMD Athlon™ XP 3200+ 2.2 GHz	345 us
AMD Athlon™ 64 X2 Dual Core 4200+ 2.2 GHz	325 us

## 3 INSTALLATION

### 3.1 System Requirements

The module must be installed on an x86 or x86-64 system running a Linux distribution with a kernel of the 2.4 or 2.6 series. A working Zaptel installation is needed.

Each supported channel uses approximately 46 Kbytes of system memory.

The application and kernel module have been tested on the following configurations:

- Intel ® Pentium 4 ® 2.0 GHz CPU running Fedora Core 5.0, kernel 2.6.17
- Intel ® Pentium 4 ® 3.0 GHz CPU running Ubuntu 6.10, kernel 2.6.17
- AMD Athlon™ XP 3200+ 2.2 GHz CPU running Slackware 11.0, kernel 2.4.33
- AMD Athlon™ 64 X2 4200+ 2.2 GHz CPU running Ubuntu 6.10, kernel 2.6.17

## 3.2 Downloading Archive

The latest version of the OCTVQE8 software is always available from:

<http://www.octware.net/pub/octvqe8/>

<ftp://ftp.octware.net/pub/octvqe8/>

The latest version can be downloaded using FTP or HTTP protocol, using command line tools like *wget* or *ftp*.

Two different files are needed to build a complete package. One is the base package needed to interface with low-level Zaptel routines, the other is the actual echo cancellation service binary. The echo cancellation service binary is optimized for certain specific CPU. The appropriate package file should be downloaded according to the target CPU.

## 3.3 Archive Contents

The compressed OCTVQE - Zaptel Echo Cancellor archives (in .tgz format) can be decompressed using the following command in a shell window:

```
[root@localhost temp_dir]# tar -zxpf octvqe8-01.00.00-base.tgz
[root@localhost temp_dir]# tar -zxpf octvqe8-01.00.00-<arch>.tgz
```

Here are the contents of these archives:

Filename	Description
octvqeug5000-xxx.pdf	This document, the application's user guide.
ReleaseNotes.txt	Release notes.
README	Readme file containing brief installation instructions.
octwareec12.h, octwareec14.h	These header files provide the hooks for the OctWare Echo Cancellor into the Zaptel interface. octwareec12.h is used with Zaptel version 1.2, octwareec14.h is used with Zaptel version 1.4.
octvqe/octvqe_linux.c, .h	The OCTVQE kernel module source files.
octvqe/octvqe_ioctl.h	The OCTVQE kernel module I/O control defines, for channel statistics.
octvqe/Makefile	Makefile necessary to compile the OCTVQE kernel module.
octvqe/octvqed	The echo cancellation and VQE service binary.
octvqe/octvqed.init	Script to make the service auto-loading at system start-up.
octvqe/octvqed.conf	Channel parameters configuration file.

Upon receiving the OCTVQE - Zaptel Echo Cancellor archives:

1. Extract the archives contents and verify that all the files listed above are present.
2. Read through ReleaseNotes.txt for backward compatibility and version-specific information.

## 3.4 Building and Installing the Octvqe Module

Since it is necessary to build the module for the Linux kernel running on the target machine, the package provides the necessary source files to do so.

In principle, the module should be compiled whenever the version of the Linux kernel is changed on the target machine. To compile the module, the corresponding Linux kernel source tree must be installed on the compiling machine.

Compiling the *octvqe* kernel module also requires the Zaptel source to be available. The source includes the default echo canceller that ships with Zaptel. This echo canceller will be used when the *octvqed* service is not running. The following guidelines assume that the Zaptel source code is located in */usr/src/zaptel*.

Run the following commands as root in a terminal in order to compile and install the *octvqe* kernel module:

```
[root@localhost temp_dir]# cd octvqe8-01.00.00
[root@localhost octvqe8-01.00.00]# cp -rf octvqe /usr/src/zaptel
[root@localhost octvqe8-01.00.00]# cd /usr/src/zaptel/octvqe
[root@localhost octvqe]# make
[root@localhost octvqe]# make install
[root@localhost octvqe]# killall octvqed
[root@localhost octvqe]# rmmod octvqe
[root@localhost octvqe]# depmod
[root@localhost octvqe]# modprobe octvqe
```

**NOTE:** The '*killall octvqed*' and '*rmmod octvqe*' commands are only required if upgrading from a previous version. Please make sure to also remove any module that depends on the *octvqe* module as well (for example, *zaptel*).

## 3.5 Rebuilding and Installing the Zaptel Module

Since the default Zaptel installation does not contain the OctWare OCTVQE software, the Zaptel source files must be modified and recompiled. This allows Zaptel to use the *octvqed* application for echo cancellation. Again, the following guidelines assume that the Zaptel source code is located in */usr/src/zaptel*. Here are the steps to follow in order to rebuild and install the Zaptel module.

Copy the *octwareecXX.h* (replace XX by 12 when you have Zaptel 1.2.12 or lower, or 14 when your version of Zaptel is above 1.2.12) file and the include directory from the installation package to the Zaptel source directory:

```
[root@localhost octvqe8-01.00.00]# cp octwareecXX.h /usr/src/zaptel
[root@localhost octvqe8-01.00.00]# cd /usr/src/zaptel
```

Edit the *zconfig.h* file in order to define OctWare's echo canceller. Search within this file for the keyword *ECHO\_CAN* and replace the default echo canceller with the OctWare echo canceller by commenting out the built-in echo canceller and adding the following line:



```
#define ECHO_CAN_OCTWARE
```

Edit a Zaptel source file to include OctWare's echo canceller. The Zaptel source file to edit depends on the version of Zaptel in use. If the version of Zaptel is 1.2.12 or lower, *zaptel.h* needs to be edited; if the base version is 1.4, *zaptel.c* needs to be edited; if the version is 1.2.13, *zaptel-base.c* needs to be modified. Search for the ECHO\_CAN keyword and add the following lines (replace XX by 12 or 14 depending on your version):

```
#elif defined(ECHO_CAN_OCTWARE)
#define ZAPTEL_ECHO_CANCELLER "OCTEC" /* Only used in zaptel.h or .c */
#include "octwareecXX.h"
```

Run the following commands to compile and install the Zaptel drivers with the new echo canceller:

```
[root@localhost zaptel]# make
[root@localhost zaptel]# make install
```

Remove the old Zaptel module (as well as any other Zaptel dependent modules) and reload the newly created Zaptel module:

```
[root@localhost zaptel]# rmmod zaptel
[root@localhost zaptel]# modprobe zaptel
```

## 3.6 Registering the Octvqed Service

In the case where a per-channel license service is used (OCTVQE8 package), a registration utility needs to be used to download a license that activates channels. This has to be done only once, before starting the *octvqed* service for the first time. Additional channel licenses can be purchased and activated at any time.

The registration utility can be downloaded from:

<http://www.octware.net/pub/register/>

<ftp://ftp.octware.net/pub/register/>

The registration procedure is detailed below.

First, change the permissions of the register utility file found in the package source directory. Change the user and group ownership of the file to "root".

```
[root@localhost octvqe8-01.00.00]# chmod 500 register
[root@localhost octvqe8-01.00.00]# chown root.root register
```

Internet access is required from the ZapTel installation host to be able to register the OCTVQE software for licensed use. Outgoing traffic on TCP (enough permission to open an SSL session) must be allowed in order for the register utility to successfully communicate with OctWare's license server and finalize the registration process. Also, the name of the first ethernet device found on the host that will run the OCTVQE software must be "eth0", for the registration sequence to complete. The other Ethernet devices found on the system are not considered when generating the license. Run the application:

```
[root@localhost octvqe8-01.00.00]# ./register
```

If the register utility starts up correctly, enter the Activation-Key that you have purchased. Follow the on-screen instructions.

Repeat the same procedure if more than one license needs to be generated. The utility also supports a "batch" activation mode, where the Activation-Keys are passed to the application using a file, one Activation-Key per line. Use the -b option.

Optionally, the generated licenses can be verified using the -p argument to the register utility:

```
[root@localhost octvqe8-01.00.00]# ./register -p
OctWare Product Registration Utility
Copyright (C) 2007, OctWare Inc.
Reading directory '/var/lib/octware/licenses'...
Product OCTVQE8 (quantity 2) found in file OCTVQE8-OCT-XXXXXXXXXXXX-2.lic
Product OCTVQE8 (quantity 1) found in file OCTVQE8-OCT-XXXXXXXXXXXX-1.lic
```

The register application is used for all OctWare products. Therefore, licenses for other products may appear in this list when the -p argument is used. The register utility will print the information for all license files found in the `/var/lib/octware/licenses` directory.

It is **EXTREMELY** important to **BACKUP** the files found in `/var/lib/octware/licenses` directory. This directory contains the Host-ID specific license files for the current system. These licenses are locked to the MAC address of the Ethernet devices found on the system. Creating a backup of this directory will allow a complete restoration of the OCTVQE channels that were licensed using the register utility when doing a new operating system installation. This will prevent unnecessary interactions with your key distributor, requesting authorization to increment the Activation-Key that was already used.

Here are the register utility command line options:

- b FILE: Read activation keys from FILE.
- h: Display the help menu and exit.
- l: Display the license information for the program and exit.
- p: Display the licenses installed on this host.
- v: Print the version of the register utility, openssl toolkit and curl library.

## 3.7 Starting the Octvqed Service

Start the echo cancellation service simply by running *octvqed* as root. The application will detach from the calling terminal and will run in the background.

```
[root@localhost octvqe]# ./octvqed
```

Here are the available command line options:

- c NUM:        Start the *octvqed* service using NUM channels.
- f CONFIG:     Read channel configuration from config file CONFIG.
- h:            Display the help menu and exit.
- l:            Display the license information for the program and exit.
- v:            Print the version of the *octvqed* daemon and the version of the OCTVQE API and exit.
- x:            Run *octvqed* in debug mode, the server will not detach from the terminal.

## 3.8 Automatic Startup Script

The OCTVQE service can be automatically loaded at startup using an init script. The procedure outlined below must be followed to have the service automatically launched when the host boots.

First, the *octvqed* application binary must be permanently installed on the host. We recommend installing the *octvqed* file in the */usr/sbin/* directory:

```
[root@localhost octvqe]# cp octvqed /usr/sbin/
```

Then locate the init script example in the package's *octvqe* directory. This file should be copied and renamed to your system's initialization directory, where the init procedure launches all service processes. The file name should be the same as the name of the service, *octvqed*. Under Fedora Core, this is in the */etc/rc.d/init.d/* directory:

```
[root@localhost octvqe]# cp octvqed.init /etc/rc.d/init.d/octvqed
[root@localhost octvqe]# chown root.root /etc/rc.d/init.d/octvqed
[root@localhost octvqe]# chmod 755 /etc/rc.d/init.d/octvqed
```

Changing the file permissions to executable instructs the system's init procedure that this script is executable when the system is booting. If the *octvqed* application executable has been installed into a directory different from */usr/sbin/*, edit *octvqed.init* to reflect the changes. Then instruct the operating system that this new service should started and stopped automatically:

```
[root@localhost octvqe]# chkconfig --add octvqed
[root@localhost octvqe]# chkconfig octvqed on
```

The script can be used to control the OCTVQE service, with the following arguments:

start:	Starts the OCTVQE service.
stop:	Stop the OCTVQE service.
restart:	Stop and Start the OCTVQE service.

Alternatively, most distributions support the */etc/rc.d/rc.local* user initialization script. The OCTVQE service could be started using this file, however this will not kill octvqed very cleanly during a reboot or shutdown.

Since starting service processes at boot time differs among distributions, it is best to consult the OS documentation for how to do this.

## 4 CHANNEL CONFIGURATION

### 4.1 Default Configuration

By default, the echo cancellation channels are configured like this:

Parameter	Value	Description
Tail Length	64 ms	Maximum tail length used by the echo canceller. For optimal results this value should not be set higher than the longest expected echo path delay.
Default ERL	9 dB	The default ERL in decibels that is assumed by the NLP when not converged, e.g. at the beginning of a call.

The default parameter values are set such that the best subjective results are achieved under most conditions. The defaults can be overridden with a configuration file, as detailed below.

### 4.2 Configuration File

It is possible to change the default channel parameter values by using a configuration file passed with the `-f` argument to the *octvqed* service. The format of the configuration file is very similar to the configuration files used in Zaptel. The table below lists the parameters that can be configured using the file:

Parameter	Value/Range	Comment
taillength	32 to 128 ms in steps of 16 ms	See description in default configuration table.
defaulterl	-21 to +21 dB in steps of 3 dB	See description in default configuration table.
channel	1-8	Channel number, range or list to which the above configuration applies, for taillength, and defaulterl.

Refer to the included *octvqed.conf* file for an example configuration file.

## 5 STATISTICS

Channel-specific configuration and statistics can be retrieved via the */proc* filesystem. When the OCTVQE module loads, a */proc/octvqe* entry is created in the virtual filesystem. This entry can be used for displaying channel information. A typical output looks like:

```
[root@localhost ~]# cat /proc/octvqe
OCTVQE-MOD-01.00.00, built on Dec 1 2006 09:56:44
Channel 1 (Active)
  Tail Length (64 ms), Default ERL (9 dB)
  Rin/Sin Current Energy (-60 dB, -24 dB), Av. Energy (-37 dB, -25 dB)
  Number Buffers Processed (4325), Size 20 ms, Av./Max CPU Time ( 0 us, 0 us )
Channel 2 (Active)
  Tail Length (64 ms), Default ERL (9 dB)
  Rin/Sin Current Energy (-45 dB, -18 dB), Av. Energy (-33 dB, -32 dB)
  Number Buffers Processed (9842), Size 20 ms, Av./Max CPU Time ( 0 us, 0 us )
...
```

This output contains, among other things, the OCTVQE kernel module version, build date, current and average voice energy levels and number of processed buffers.

## 6 SOFTWARE UPDATE

Software updates will be made available through OctWare's FTP and web site, at the following URLs:

<http://www.octware.net/pub/octvqe8/>

<ftp://ftp.octware.net/pub/octvqe8/>

Please make sure to read the instructions enclosed in the new .tgz files when upgrading the OCTVQE software.

## 7 REVISION HISTORY

Version	Date	Changes
1.6	March 2007	Instructions to include the Zaptel echo canceller added. Procedure for upgrading from an old version added.
1.5	February 2007	Initialization script clarifications. Performance metrics added.
1.4	February 2007	Minor formatting changes. OctWare logo added. Instructions for downloading archive. Changed default configuration values.
1.3	February 2007	Reviewed for clarity. Online link information added.
1.2	February 2007	Added OCTVQE8 model, registration instructions. Added configuration file section. Added statistics section.
1.1	February 2007	Installation instructions and package content.
1.0	November 2006	Initial release.



For more information on this or other products visit our web site: <http://www.octware.net/>

Or contact us at:

**OCTWARE Inc.**  
4101 Molson St, Suite 300  
Montreal, Quebec  
H1Y 3L1, Canada